

## Re-survey Subdivisional Lines, T.2 S., R.34 E., W. M.

Chains		Feet								
	for witness Cor. to $\frac{1}{4}$ Sec. Cor., with brass cap, marked,									
	$\frac{1}{4}$ S22   S23 WC 1917									
	The true course & dist., of this line to $\frac{1}{4}$ Secs. Cor. is									
	N.0°07'E., 39.88 chs.									
	Thence									
	N., continuing my line and measurements.									
79.67	Fall 28 lks. W. of Cor. of Secs. 14, 15, 22 & 23, the position of which is determined by the original bearing tree.									
	At exact point									
	Set iron post, 3 ft. long, 2 ins. diam., 24 ins. in ground, for Cor. of Secs. 14, 15, 22 & 23, with brass cap, marked,									
	<table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td>T23</td> <td>R34E</td> </tr> <tr> <td>S15</td> <td>S14</td> </tr> <tr> <td>S22</td> <td>S23</td> </tr> <tr> <td colspan="2" style="text-align: center;">1917</td> </tr> </table>	T23	R34E	S15	S14	S22	S23	1917		
T23	R34E									
S15	S14									
S22	S23									
1917										
	from which,									
	A pine, 12 ins. diam., brs. S.35°W., 25 lks. dist., marked S.22,R.34 E., B.T. (Old B.T.)									
	(Unable to find any of the other original bearing trees)									
	A tamarack, 12 ins. diam., brs. N.7°30'E., 82 lks. dist., marked T.2 S., R.34 E., S.14, B.T. (New B.T.)									
	A fir, 8 ins. diam., brs. S.46°30'E., 31 lks. dist., marked T.2 S., R.34 E., S.23, B.T. (New B.T.)									
	A yellow pine, 12 ins. diam., brs. N.65°W., 28 lks. dist., marked T.2 S., R.34 E., S.15, B.T. (New B.T.)									
	The true course & dist. of this line from the $\frac{1}{4}$ Sec. Cor. is N.0°17'E., 39.79 chs.									
	Land; rolling.									
	Soil; rocky clay loam, 3rd rate.									
	Timber; pine, fir and tamarack.									
	Undergrowth; fir and pine.									
	N.89°55'W., retracing bet. Secs. 15 & 22.									
	Over rolling land, through scattering timber and undergrowth.									
40.21	Fall 12 lks. S. of $\frac{1}{4}$ Sec. Cor., the position of which is									