Resurvey Subdivisional Lines, T.2 S., R.34 E., W. M.

	Chai ns	determined by the original bearing trees. At the exact	Fee
	er des positi	Cor. point	
l		Set iron post, 3 ft. long, 1 in. diam., 26 ins. in ground,	
	- 3	for ½ Sec. Cor., with brass cap, marked,	1
	•	1 S15 2 S22 1917	1
	**	from which,	*
		A fir, 20 ins. diam., brs. N.5°E., ll lks. dist.,	100
	* *	marked & S., B.T. I mark it 15 (Old B.T.)	177
1		A lodgepole pine, 8 ins. diam., brs. S.13°E., 16 lks.	
		dist., marked 2 S., B.T. I mark it 22 (Old B.T.)	
		This Cor. is located at Cor. of fences bearing W. & S.	
	60.39	Cor. of fences, which extend E. & N.	
	80.45	Fall 24 lks. S. of Cor. of Secs. 15, 16, 21 & 22, which is	
		basalt stone, 6 x 6 x 2 ins., above ground, firmly set	
		(apparently recently), marked with a cross (X) on top,	
		3 notches on E. & S. edges; from which,	
-		A pine, 16 ins. diam., brs. N.43°E., 792 lks. dist.,	
1		marked S.16, B.T. I remark it T.2 S., R.34 E., S.15, B	т.
	- 534	A fir, 10 ins. diam., brs. S.46°E., 41 lks. dist., mark	
	20 8	ed S.21, B.T. I remark it T.2 S., R.34 E., S.22, B.T.	
		A tamarack, 10 ins. diam., brs. S.23°W., 61 lks. dist	.,
	× V	marked S.22 B.T. I remark it E.2 S., R.34 E., S.21, B	1000
		A tamarack, 18 ins. diam., brs. N.52°30'W., 43 lks.	
	8 31	dist., marked S.15 B.T. I remark it T.2 S., R.34 E.,	
	S 200 2	S. 16,B.T.	
	A	The true course & dist. of this line is N.89°45'W.,80.45	
		chs. (west half, 40.24 chs.)	
		Land; rolling.	
		Soil; rocky, 4th rate.	
		Timber; pine, fir and tamarack.	
		Undergrowth; pine & fir.	
		N., retracing bet. Secs. 15 & 16.	
		Over rolling land; through scattering timber & undergrowth	1.
	70,00	Fall 19 1ks. W. of \$ Sec. Cor., which is basalt stone, 12 x	