

Exterior Lines Tp. 4 S., R. 32 E.

Chains	Feet
	marked T 3 S., R 33 E.S. 30 BT. A Pine 16 in. diam. brs. S. 16° W. 169 lks dist., marked T. 3 S., R. 32 E. S. 36 B.T. A Pine 18 ins. diam. brs. N. 8° W. 241 lks dist. marked T. 3 S., R. 32 E. S. 25 B. T. No tree S.E. raised a mound of stone in line of pit. Land; surface slightly rolling, Soil; 3rd and wnd rate, Pine, tamarack and Fir timber with some under brush, Pine, Tamarack, Fir, some open glades.
	N. on the range line along the E. Bdy. of Sec. 25, Var. 20° 45' E
39.25	A Spring branch, course. N. E.
40.00	Set a basalt stone 10 x 8 x 7 in 7 In. in ground on S.E. slope for $\frac{1}{4}$ Sec. Cor., marked $\frac{1}{4}$ on W. face from which, A Tamarack 8 in. diam brs. S. 71° E. 96 lks dist. marked $\frac{1}{4}$ S. BT. A Pine 8 ins. diam. brs. S. 36° W. 69 lks dist., marked $\frac{1}{4}$ S. B T.
	Descending,
80.00	Descent about 200 ft. Set a basalt stone 16 x 12 x 10 ins. 11 ins. in ground on E. slpe for Cor. to Secs. 24, 25, 19 and 30. Marked with 2 notches on S. and 4 notches on N. edges from which, A Tamarack 8 ins. diam. brs. N. 68° E. 46 lks dist. Marked T. 3 S. R. 33 E. S 19 B T. A Pine 5 ins. diam brs. S. 40° E. 26 lks dist. Marked T. 3 S., R 33 E. S. 30 B.T. A Pine 6 ins. diam brs. S. 42° W. 24 lks dist. Marked T. 3 S., R. 32 E. S. 25 B.T. A Pine 4 ins. diam. brs. N. 45° W. 31 lks. dist. Marked T. 3 S., R. 32 E. S. 24 B.T. Land; surface broken and rolling, Soil; 2nd and 3rd rate, heavily timbered with Pine, Tamarack