Subdivisional Lines of T. 3 S., R. 32 E

	Chains	9 16	Fe
	28.00	A brook 6 lks. wide, course N.W. (same)	
	40.00	Set temp. 2 Sec. Cor.	
	60.50	A spring branch, course S.W.	
	79.82	Intersected E. Bdy 14 lks. S. of Cor. to Secs. 13 and	
	1 to 1	24, which is a stone 14 x 10 x 8, marked with 3 notches	- 00
	ar es	on N. and S. edges from which,	
		A Pine 10 ins. diam. brs. N. 38° E. 60 lks. dist.	
		Marked T. 3 S., R. 33 E., S. 18 B.T.	
0	-	A Pine 10 ins. diam. brs. S. 72° E. 43 lks. dist.	
		Marked T. 3 S., R. 33 E., S. 19 B.T.	
		A Pine 6 ins. diam. brs. 28° W. 45 lks. dist.	
ŧ		. Marked T. 3 S., R. 32 E., S. 24 B.T.	
0		A Pine 6 ins. diam. brs. N. 45° W. 31 lks. dist.	
8		Marked T. 3 S., R. 32 E., S. 13 B.T.	
	20 .	from which Cor. I run,	
		S. 89° 54' W. on a true line bet. Secs. 13 and 24,	
		Var. 24° 15' E	
	39.91	Set a basalt stone 15 x 8 x 5 ins. 10 ins. in ground on	
		S. slope for & Sec. Cor. marked & on N. face,	
		A Pine 10 ins. diam. brs. S. 18° E. 156 lks. dist.	
901	11 11 11 11	Marked & S. B.T.	
	B. S	No trees N., raised mound of stone alongside of Cor.	
		instead.	
	79.82	The Cor. to Secs. 13, 14, 23 and 24.	
. 1	13.02	CES OF STATE	
		Land; surface rolling and broken,	
		Soil; 3rd rate, irregular Pine, Tamarack and Fir timber,	
	7	with open glades. Some undergrowth, Pine, Tamarack	
		and Fir.	
	2	May 16, 1882.	
-		N. N. L. C.	
	* 11	N. bet. Secs. 13 and 14.	
		Var. 21° 00' E	
	10.25	Along up W. hillside,	
8	40.00	Set a basalt stone 14 x 8 x 7 ins. on W. slope 10 ins.	į.
	- 5	in ground for & Sec. Cor. , marked & on W. face,	