00.

	Chains		F
2		33 of Tp: 2 S., R. 32 E., ascent about 100 ft.,	
		Set a basalt stone 18 x 10 x 7 ins. 12 ins. in ground	
J	7	on N.W. slope at intersection for Cor. to Secs. 3 and	
		4, marked with 6 notches on S. and 3 notches on E.	
	150	edges.	
	a	A Pine 14 ins. diam. brs. N. 38° W. 112 lks. dist.	
	a .	Marked T. 3 S., R. 32 E., C.C. B.T.	
		No other trees, raised mound of stone alongside in liew	
	1760	of pits.	
		Note: - I marked these fors. in this way, to prevent-	
	917	confusion.	
		Land; surface very broken,	
		e 353 8	
12		Soil; 2nd and 3rd and small part 1st rate, A few scat-	
		tering Pine trees. Good grass.	
		May 22, 1882	
		The state of the control of the cont	
		From the Cor. to 32 and 33 which is a stone 16 x 10 x	
		4, marked with 4 notches on E.edge,	
#3		A Tamarack 13 lks. diam. brs. N. 85° E. 20 lks. dist.	
		Marked T. 3 S., R. 32 E., S. 33 B.T.	
		A Tamarack 4 ins. diam. brs. S. 36° E. 25 lks. dist.	
		Marked T. 4 S., R. 32 E., S. 4 B.T.	
		No trees S.W.	
		A Pine 28 ins. diam. brs. N. 39 W. 97 lks. dist.	
	8 19	Marked T. 3 S., R. 32 E., S. 32 B.T.	
		I run,	
		N. bet. Secs. 32 and 33,	
	1602	Var.	
	21.00	Wagon road, course E. and W. to Hot Sulphur Springs.	
	27.50	A spring branch, course N.W.	
	40.00	Set a basalt stone 18 x 16 x 5 ins. 12 ins. in ground	
	ces	on S.W. slope for & Sec. Cor., marked & on W. face.	
		A Pine 16 ins. diam. brs. N. 85° E. 165 lks. dist.	
	-	Marked & S.B.T.	
		A Pine 28 ins. diam. brs. N. 61° W. 174 lks. dist.	