

N. Bdy., T.4 S., R.33 E., W. M.
As surveyed by Geo. S. Pershin, U.S. Deputy Surveyor,
Under Contract No. 410,
Dated July 28, 1881.

Chains	Feet
	From the Cor. to Tps. 3 & 4 S., Rs. 32 & 33 E., which is a basalt stone, 20 x 8 x 4 ins., marked with 6 notches on N., S., E. & W. edges, from which A pine, 8 ins. diam., brs. N.32°E., 9 lks. dist., marked T.3 S., R.33 E., S.31, B.T. A pine, 10 ins. diam., brs. S.36°E., 31 lks. dist., marked T.4 S., R.33 E., S.6, B.T. A pine, 7 ins. diam., brs. S.28°W., 4 lks. dist., marked T.4 S., R.32 E., S.1, B.T. A fir, 5 ins. diam., brs. N.42°W., 62 lks. dist., marked T.3 S., R.32 E., S.36, B.T.
	I run
	S.89°50' E. on true line on N. Bdy. of Secs. 6. Var. 15°30' E.
3.20	A spring branch, course S.; descent 80 ft.
38.38	Set basalt stone, 20 x 10 x 4 ins., on level, in small md. of stone, for $\frac{1}{4}$ Sec. Cor., marked $\frac{1}{4}$ on N. face, from which, A pine, 10 ins. diam., brs. N.60°E., 10 lks. dist., marked $\frac{1}{4}$ S., B.T. A pine, 36 ins. diam., brs. S.43°W., 117 lks. dist., marked $\frac{1}{4}$ S., B.T.
	Ascent 100 ft.
78.38	Set basalt stone, 18 x 10 x 3 ins., 12 ins. in ground, for Cor. to Secs. 5, 6, 31 & 32, marked with 5 notches on E. and 1 notch on W. edges, from which, A pine, 5 ins. diam., brs. N.60°E., 19 lks. dist., marked T.3 S., R.33 E., S.32, B.T. A tamarack, 12 ins. diam., brs. S.12°E., 13 lks. dist., marked T.4 S., R.33 E., S.5, B.T. A pine, 7 ins. diam., brs. S.62°W., 23 lks. dist., marked T.4 S., R.33 E., S.6, B.T. A tamarack, 10 ins. diam., brs. N.58°W., 11 lks. dist., marked T.3 S., R.33 E., S.31, B.T.
	Land; surface rolling. Soil; 3rd & 2nd rate. Heavy pine, tamarack & fir timber, with open glades.