

N. Bdy., T.4 S., R.33 E., W. M.

Chains	Feet
48.75	Spring branch, coarse S.E.
80.00	Set basalt stone, 16 x 10 x 5 ins., 11 ins. in ground, for
80.00	Cor. to Secs. 3, 4, 33 & 34, marked with 3 notches on E. & 3 notches on W. edges, from which,
	A pine, 12 ins. diam., brs. S.82°E., 113 lks. dist., marked T.4 S., R.33 E., S.3, B.T.
	A pine, 20 ins. diam., brs. N.40°W., 168 lks. dist., marked T.3 S., R.33 E., S.33, B.T.
	No other trees within distance; raised mound of stone along- side of Cor. in lieu of pits.
	Land; surface rolling.
	Soil; 3rd & 2nd rate.
	Heavy pine, tamarack & fir timber, with open glades; some dense groves of young timber.
	S.89°50'E. on true line on N. Bdy. of Sec. 3.
	Var. 19°30'E.
40.00	Set basalt stone, 17 x 8 x 6 ins., 12 ins. in ground, for Sec. Cor., marked $\frac{1}{4}$ on N. face.
	A fir, 11 ins. diam., brs. N.60°E., 37 lks. dist., marked $\frac{1}{4}$ S., B.T.
	A pine, 12 ins. diam., brs. S.3°W., 8 lks. dist., marked $\frac{1}{4}$ S., B.T.
59.50	A spring branch, coarse S.E.
80.00	Set basalt stone, 16 x 10 x 5 ins., 11 ins. in ground, for Cor. to Secs. 2, 3, 34 & 35, marked with 2 notches on E. and 4 notches on W. edges, from which,
	A pine, 24 ins. diam., brs. S.21°E., 136 lks. dist., marked T.4 S., R.33 E., S.2, B.T.
	A pine, 10 ins. diam., brs. S.51°W., 89 lks. dist., marked T.4 S., R.33 E., S.3, B.T.
	A pine, 8 ins. diam., brs. N.69°W., 68 lks. dist., marked T.3 S., R.33 E., S.34, B.T.
	No tree, N.E., open glade. Raised mound of stone alongside of Cor. in lieu of pits.
	Land; surface rolling, Soil; 3rd & 2nd rate.
	Pine, tamarack & fir timber, with open glades.