Resurvey of portion of the E. Bdy. of T. 4 N., R. 38 E., W.M.

Chains	Fe
	Undergrowth; willow, maple and wild berry.
	Mountainous or heavily timbered land or land covered with
2	dense undergrowth and exceptionally difficult to survey.
	77.25 chs.
= -	
	S. 0° 9' W. on a resurvey bet. Secs. 7 & 12.
	Descend over precipitous ground.
40.34	Intersect the old \(\frac{1}{4} \) sec. cor., which is a basalt stone,
	15 x 10 x 5 ins., marked as described by the surveyor
	general. I re-establish the cor. at the same point as
	follows:
4	Set a basalt stone, 15 x 10 x 5 ins. 10 ins. in the ground
	for $\frac{1}{4}$ Sec. Cor., marked $\frac{1}{4}$ on W. face, from which:
32 10	A pine, 40 ins. in diam. brs. S. 76° E., 295 lks. dist.
18 E	marked ½ S 7 B T
	and raised a mound of stone, 2 ft. base and 1 ft. and
	a half high, W. of Cor.
	No tree W. of the line within limits.
	Therefore the N. half of this line is 40.34 chs. in length
	and brs. S. 0° 9! W. I continue the re-survey S. 34. W.
	Descend over precipitous ground.
60.84	Foot of descent, 150 ft. below Sec. Cor.
00.04	Control Security Control Contr
	Walla Walla River, 50 lks. wide, course W.
04.04	Begin steep precipitous ascent.
84.84	Intersect the old cor. for secs. 7, 12, 13 & 18, which is
	a basalt stone, 15 x 10 x 5 ins. The bearing tree describ-
	ed by the surveyor general as a fir 16 ins. diam. bearing
	N. 33° E., 138 lks. dist. is dead. I re-establish the
	Cor. at the same point as follows:
	Set a basalt stone, 15 x 10 x 5 ins. 10 ins. in the ground
	for Cor. to Secs. 7, 12, 13 & 18, marked with 2mnotches
	on the N. and 4 notches on the S. edges, from which:
	A fir, 30 ins. diam. brs. N. 45° E., 172 lks. dist.
	marked T 4 N R 38 E S 7 B T
	and raised a mound of stone, 2 ft. base and 1 ft. and a
	half high W. of Cor.