Retracement of the Subdivisional Lines of T. 4 N., R. 37 E., W.M.

	Chains		Fe
	Y.:	Timber; fir, pine, spruce and tamarack.	
		Mountainous, heavily timbered lands. 81.10 Chs.	
		June 16 1902	
		Valid 10. 1502	
20	×	Subdivisional Lines of T. 4 N., R. 37 E., W.M. As surveyed by same surveyors, date & Contract.	
		En 116 - 1 116 - 117 - 1	t
		N. 0° 01' W. bet. Secs. 23 & 24	
		Descend steep N. slope of spur, through old burn	
10	3.25		
23	7.80	Enter fir thicket, brs. N.W. and S.E.	
30	700 2	Foot of ravine, 200 ft. deep, course N. 35° E.	
	7.85	Creek, 5 lks. wide, course, N. 35° E.	
		Ascend gradually along steep E. slope of mountain.	
	11.25	Leave fir thicket, brs. N.E. and S.W.	
	15.75	Descend along steep E. slope into Elbow Canyon	
- 1	15.80	Trail, brs. N. 70° W., and S. 70° E.	
	24.00	Enter scattering timber, brs. E. and W.	
	26.25	Enter heavy timber, brs. E. and W.	
8	26.80	Foot of ravine, 50 ft. deep, course N. 30° E.	
	31.00	Abrupt descent	
	32.75	Foot of mountain, 1,000 ft. below sec. cor.	
		Over rolling bottom, not subject to unumdation.	
	33.70	Elbow Creek, 10 1ks. wide, pure cold water, stony bottom,	
20 40.		dourse N. 40° W.	
		Ascend gradually along W. slope of mountain	
	39.75	A spring branch, 2 lks. wide, in ravine, 50 ft. deep,	
3.55		course N. 70° W.	
		Ascend steep bank	
- 69	40.00	The true point for $\frac{1}{4}$ Sec. Cor., falls on unsecure grounds.	31
×	40.36	Set a basalt, 24 x 12 x 5 ins., 18 ins. in the ground for	
		and the various control of the	
	500	W.C. to \(\frac{1}{4}\) Sec. Cor., marked W.C. \(\frac{1}{4}\) on the W. face.	
x 3		from which,	70
		A tamarack, 10 ins. diam. brs. N. 27° 30' E., 17 lks. dist. marked W. C. 4 S. 24 B.T.	700
27	9	A Tamarack, 10 ins. diam., brs. N. 6° 45' W., 91 lks.	8
		dist. marked W.C., 1 S. 23 B.T.	