Resurvey of portion of the E. Bdy. of T. 4 N., R. 38 E., W. M.

| Cha  | ns Fee   | et |
|------|--|----|
|      | In the retrace I find the old line of the E. Bdy. oblitere                         |    |
|      | ated and the Cors. badly delapidated, and in most intances                         |    |
|      | almost completely destroyed. Therefore I return on a re-                           | 0  |
|      | survey of a portion of the E. Bdy. of the Tp. From the                             |    |
|      | Closing Cor. of tps. 4 N Rs. 38 & 39 E., which is a bas-                           | ~  |
|      | alt stone, 6 x 8 x 6 ins. above ground marked and wit-                             |    |
|      | tnessed as described by the surveyor general. I run                                |    |
|      | S. 1° 8' W. on a resurvey bet. Secs. 1 & 6. Descend over                           |    |
|      | precipitous ground through heavy timber and dense under-                           |    |
|      | growth.  |    |
| 13.9 |  |    |
| 19.  | V V  |    |
| 1    | is clear and cold and flows with a swift current over                              |    |
|      | stony bed. Begin steep precipitous ascent of N. slope.                             |    |
| 40.  |  |    |
| 100  | 18 x 12 x 5 ins., marked as described by the surveyor                              | ~  |
| - X  | general. The marks on the witness trees are overgrown.                             | -  |
| - 1  | I re-establish the Cor. at the same point as follows:                              |    |
|      | Set a basalt stone, 18 x 12 x 5 ins. 14 ins. in the ground                         |    |
|      | for $\frac{1}{4}$ Sec. Cor., marked $\frac{1}{4}$ on W. face, from which           |    |
|      | A fir, 16 ins. diam. brs. N. 88° E., 105 lks. dist. marked \(\frac{1}{4}\) S 6 B T |    |
|      | A fir, 14 ins. diam. brs. N. 70° W., 83 lks. dist. marked ½ S 1 B T                |    |
| **   | Therefore the N. half of this line is 40.19 Chs. in length                         |    |
|      | and brs. S. 1° 8' W. I continue the resurvey S. 2° 22'                             |    |
|      | E., ascend over precipitous ground, through heavy timber                           |    |
|      | and dense undergrowth.   |    |
| 79.  | 4 Intersect the old Cor. for Secs. 1, 6, 7 & 12.                                   | 0  |
|      | The post described by the surveyor general is decayed and                          | -  |
|      | the bearing trees are dead. The stumps of the bearing                              |    |
|      | trees remain, from which I determine the Cor. point. I                             |    |
| - 1  | re-establish the Cor. at the same point as follows:                                |    |
| 3    | Set a basalt stone, 15 x 8 x 6 ins. 10 ins. in the ground                          |    |
|      | for Cor. of Secs. 1, 6, 7 & 12, marked with 1 notch on                             |    |
|      | the N. and 5 notches on the S. edge, from which                                    |    |
|      | A tamarack, 18 ins. in diam. brs. N. 14° E. 36 lks.                                |    |