## Subdivisional Lines of T. 4 N., R 38 E., W.M.

Chain	S
	$\frac{1}{4}$ Sec. Cor., marked $\frac{1}{4}$ on W. face, from which
	A fir, 18 ins. diam. brs. S. 80° E., 56'lks. dist. marked 4 S B T
	A fir, 20 ins. diam. brs. N. 78° W., 98 lks. dist. marked 4 S B T
43.00	Spring brook, 3 lks. wide, runs N. 5° E.
46.00	Creek, 15 lks. wide, runs E.
80.00	Set a basalt stone, 16 x 10 x 5 ins., 11 ins. in ground
	for Cor. to Secs. 21, 22, 27 & 28, marked with 2 notch
	on S. and 3 notches on E. edges from which
	A fir, 18 ins. diam. brs. N. 19° E., 84 lks. dist. marked T 4 N R 38 E S 22 B T
	A fir, 30 ins. diam. brs. S. 10° E., 82 lks. dist. marked T 4 N R 38 E S 27 B T
	A fir, 30 ins. diam. brs. S. 30° W., 52 lks. dist. marked T 4 N R 38 E S 28 B T
	A fir, 16 ins. diam. brs. N. 42° W., 138 lks. dist. marked T 4 N R 38 E S 21 B T
1	Land: rolling, densely covered with forests of pine, fir,
	and tamarack, much being dead and fallen
T P	Thick undergrowth; tamarack, fir and buckbrush. 80 Chs.
	Soil; sandy loam, 2nd rate.
1 C (1)	
	E. on random line bet. Secs. 22 & 27
	Var. 16½° E
	Descend, 200 ft.
17.00	Creek, 15 lks. wide, runs N. 10° E.
100	Ascend
1	and the contract of the contra
31.00	Spring brook, 2 lks. wide, runs N.W.
31.00	Spring brook, 2 lks. wide, runs N.W. Set temp. 4 Sec. Cor.
1500000 20000	Set temp. 1 Sec. Cor.
40.00	
40.00	Set temp. ½ Sec. Cor.  Top of ridge, course N. & S., 500 ft. above creek and descend 100 ft.
40.00	Set temp. 1 Sec. Cor.  Top of ridge, course N. & S., 500 ft. above creek and
40.00	Set temp. 4 Sec. Cor.  Top of ridge, course N. & S., 500 ft. above creek and descend 100 ft.  Intersect N. and S. line at the Cor. to Secs. 22, 23, 26 & 27, with same var.
40.00 65.00 80.17	Set temp. 4 Sec. Cor.  Top of ridge, course N. & S., 500 ft. above creek and descend 100 ft.  Intersect N. and S. line at the Cor. to Secs. 22, 23, 26 & 27, with same var.  Set a basalt stone, 10 x 10 x 8 ins., 7 ins. in ground
40.00 65.00 80.17	Set temp. ½ Sec. Cor.  Top of ridge, course N. & S., 500 ft. above creek and descend 100 ft.  Intersect N. and S. line at the Cor. to Secs. 22, 23, 26 & 27, with same var.  Set a basalt stone, 10 x 10 x 8 ins., 7 ins. in ground for ½ Sec. Cor., marked ½ on N. face, from which  A tamarack, 6 ins. diam. brs. N. 10° E., 17 lks.
40.00 65.00 80.17	Set temp. ½ Sec. Cor.  Top of ridge, course N. & S., 500 ft. above creek and descend 100 ft.  Intersect N. and S. line at the Cor. to Secs. 22, 23, 2 & 27, with same var.  Set a basalt stone, 10 x 10 x 8 ins., 7 ins. in ground for ½ Sec. Cor., marked ½ on N. face, from which