

Exterior Lines of T. 4 S., R. 29 E. W.M.

Chains		Feet
	on steep S.W. face of hill in float rock. Raised a mound of stone around Cor. stone and post, pits impracticable. Cor. of T. 3 S., R. 29 and 30 E. is 382 lks. W. of stone Cor. to T. 3 S., Rs. 29 and 30 E.	
	Land; surface rolling, Soil; 2nd and 3rd rate, some scattering pine, timber. mostly open, good grass.	
		June 8, 1882.
	<hr/> Exterior Lines of T. 4 S., R. 30 E., W.M. As surveyed by George S. Pershin, U.S. Deputy Surveyor, Under Contract No. 430, Dated March 23, 1882.	
	I begin at the Cor. to Tps. 4 and 5 S., Rs. 30 and 31 E., which is a stone, marked with Six notches on N.E.S. and W. edges, from which,	
	A Pine 20 ins. diam. brs. N. 56° E. 54 lks. dist. marked T. 4 S., R. 31 E., S. 31 B.T.	
	A Pine 22 ins. diam. brs. S. 33° E. 118 lks. dist. marked T. 5 S., R. 31 E., S. 6 B.T.	
	A Pine 16 ins. diam. brs. N. 60° W. 80 lks. dist. marked T. 4 S., R. 30 E., S. 36 B.T.	
	A Pine 18 ins. diam. brs. N. 30° W. 80 lks. dist. marked T. 4 S., R. 30 E., S. 36 B.T., Thence I run, W. on a random line along the S. Bdy. of Secs. 36, 35, 34	
	33, 32 and 31. Var. E.	
	And at 5 miles, 78 Chs. and 72 lks. I intersected W. Bdy, 120 lks. S. of Cor. to Tps. 4 and 5 S. R. 29 & 30 E., which is a post 4 ins. sq., marked with 6 notches on N.E. S. and W. edges and marked T. 4 S., R. 30 E., S. 31 on N.E. T. 5 S., R. 30 E., S. 6 on S.E., T. 5 S., R. 29 E., S. 1 on S.W. and T. 4 S., R. 29 E., S. 36 on N.W.	
	A Pine 9 ins. diam. brs. N. 62° E. 19 lks. dist. marked T. 4 S., R. 30 E., S. 31 B.T.	
	A Pine 9 ins. diam. brs. S. 34° E. 21 lks. dist. marked T. 5 S., R. 30 E. S. 6 B.T.	
	A Pine 9 ins. diam. brs. S. 68° W. 32 lks. W. marked T. 5 S., R. 29 E. S. 1 B.T.	
	A Pine 8 ins diam. brs. N. 44° W. 8 lks. dist. marked T. 4 S., R. 29 E., S. 36 B.T.	
	My correction will be 20 lks. per mile, S. 89° 51' E. on a true line along the S. Bdy. of Sec. 31. Var. 19° 00' E	
17.50	A brook, 4 lks. wide, course S.E.	
38.72	Set a basalt stone 18 x 8 x 5 ins. in mound of stone on	