C	hains	
		of T. 3. S., R. 30 E.
	3	At intersection set a post 4 ft. long 5 ins. diam.
		flattened on S.E. and S.W. sides in mound of stone on
		S.E. slope for Cor. to Secs. 2 and 3, marked,
		T. 4 S., S. 2 on S.E. and
		R. 30 E., S. 3 on S.W.
	100	North side blank.
		Land; surface broken,
Ĭ,	. 1	W. Commission of the Commissio
		Soil; 2nd and 3rd rate, Pine, Tamarack and Fir timber,
	TE T	but mostly open. Good grass.
		June 14, 1882.
		From the Cor. to Secs. 33 and 34 which is a stone 16 x
		10 x 4 ins., marked with 3 notches on E. and W. edges,
		from which,
		A Pine 10 ins. diam. brs. N. 38° E. 126 lks. dist.
		marked T. 4 S., R. 30 E., S. 34 B.T.
		A Pine 9 ins. diam. brs. S. 39° E. 47 lks. dist.
		marked T. 5 S., R. 30 E., S. 3 B.T.
		A Pine 24 ins. diam. brs. S. 37° W. 15 lks. dist.
		marked T. 5 S., R. 30 E., S. 4 B.T.
	*	A Pine 22 ins. diam. brs. N. 45° W. 18 lks. dist.
1		marked T. 4 S., R. 30 E., S. 33 B.T.
		Thence I run,
	4	N. bet. Sec. 33 and 34,
	8	Var. 17° 30' E.
		Slightly undulating,
4	0.00	Set a basalt stone 15 x 12 x 10 ins. 10 ins. in ground
		on level in large open glade for 1 Sec. Cor., marked
		on W. side. No trees, raised mound of stone along
	8	side.
	80.00	Set a basalt stone 18 x 10 x 8 ins. 12 ins. in ground
	22.00	on level for Cor. to Secs. 27, 28, 33 and 34, marked
viii .		and the state of t
		with one notch on S. and 3 notches on E. edges.
1		A Pine 30 ins. diam. brs. S. 38° W. 158 lks. dist,,