Subdivisional Lines of T. 4 S., R. 30 E., W.M.

Chains.	t g	Feet
	Undulating,	
11.50	Wagon road, course N.E. and S.W.	
	To timber,	- (
40.00	Set a basalt stone 18 x 8 x 7 ins. in mound of stone, on	
¥2 x	N. slope on stony ground for & Sec. Cor., marked & on	
	W. face.	
68.64	Intersected N. bdy. 7.28 Chs. W. of Cor. to Secs. 32 and	
	33 of T. 3 S., R. 30 E. Set a post 4 ft. long 5 ins.	
4	diam., flattened on S.E. and S.W. sides in mound of	
	stone on E. slope at intersection for Cor. to Secs.	
	4 and 5, marked T. 4 S., S. 4 on S.E. and	
	R. 30 E., S. 5 on S.W.	
	Land; surface undulating,	
	Soil; 3rd and 2nd rate. Good grass.	
24	June 17, 1882	
	From the Cor. to Secs. 31 and 32, which is a stone 18 x	2
	10 x 5 ins., marked with 5 notches on E. and 1 notch	
	on W. edges,	
	A Pine 8 ins. diam. brs. N. 36° E. 134 lks. dist.	
	marked T. 4 S., R. 30 E., S. 32 B.T.	
	A Pine 28 ins. diam. brs. S. 70° E. 179 lks. dist.	
	marked T. 5 S., R. 30 E., S. 5 B.T.	
	A Pine 24 ins. diam. brs. S. 54° W. 102 lks. dist.	
	marked T. 5 S., R. 30 E., S 6 B.T.	
	A Pine 20 ins. diam. brs. N. 78° W. 102 lks. dist.	
02	marked T. 4 S., R. 30 E., S. 31 B.T.	
	Thence I run,	1
	North bet. Secs. 31 & 32.	
	Var. 20° 30' E.	
13.00	A slpring branch, course S.W.	r
40.00	Set a basalt stone 17 x 10 x 6 ins. 12 ins. in ground	
20.00	on slight S. slope for & Sec. Cor., marked & on W.	
	face.	
	Little State Control of the Control	
	A Pine 18 ins. diam. brs. N. 74° E. 87 lks. dist. marked & S.B.T.	