

Subdivisional Lines, T.4 S., R.33 E., W. M.

Chains	
	Thence I run N.89°51'W. on true line bet. Secs. 14 & 23. Var.17°15'E.
40.03	Set basalt stone, 16 x 10 x 5 ins., 11 ins. in ground, on level, for $\frac{1}{4}$ Sec. Cor., marked $\frac{1}{4}$ on N. face, from which A pine, 6 ins. diam., brs. S.51°W., 152 lks. dist., marked $\frac{1}{4}$ S., B.T. Open glade on N. side; raised mound of stone alongside, in lieu of pits.
80.06	The Cor. to Secs. 14, 15, 22 & 23. Land; surface slightly rolling. Soil; 3rd & 2nd rate. Pine, tamarack & fir timber, with open glades.
	Sept. 14, 1881.
	N. bet. Secs. 14 & 15. Var.17°15'E.
25.50	Open glade, course E. & W.
39.00	Enter timber, course E. & W.
40.00	Set basalt stone, 18 x 14 x 8 ins., 12 ins. in ground, for $\frac{1}{4}$ Sec. Cor., marked $\frac{1}{4}$ on W. side. A pine, 10 ins. diam., brs. S.38°E., 44 lks. dist., marked $\frac{1}{4}$ S., B.T. A pine, 26 ins. diam., brs. S.48°W., 49 lks. dist., marked $\frac{1}{4}$ S., B.T.
80.00	Set basalt stone, 16 x 8 x 7 ins., 11 ins. in ground, for Cor. to Secs. 10, 11, 14 & 15, marked with 4 notches on S. and 2 notches on E. edges, from which A pine, 8 ins., diam., brs. N.46°E., 21 lks. dist., marked T.4 S., R.33 E., S.11, B.T. A pine, 10 ins. diam., brs. S.58°E., 22 lks. dist., marked T.4 S., R.33 E., S.14, B.T. A pine, 7 ins. diam., brs. S.33°W., 25 lks. dist., marked T.4 S., R.33 E., S.15, B.T. A pine, 9 ins. diam., brs. N.45°W., 12 lks. dist., marked T.4 S., R.33 E., S.10, B.T.