

Exterior Lines, T 5 N R 39 E W M.

	Chains
	marked T 5 N R 38 E S 36 B T. A pine, 44 ins. diam., brs. S.20°W., 4 lks. dist., marked T 4 N R 39 E S 6 B T. Thence I run N. bet. Secs. 31 & 36. Var. 20°15'E.
15.30	Send flag ahead to point on line (Impossible to chain) and run Base 161 lks. E., gives an angle of 6°55'. Base multiplied by Nat. Cotan. of angle gives 73.23 lks. to flag plus 1530 lks. gives
28.53	To flag from Cor.
29.20	Top of high ridge brs. E. & W. 1000 ft. above Standard Cor. and descend.
38.60	Ravine, course E. 500 ft. below top of ridge and ascend.
40.00	Set basalt stone, 15 x 10 x 8 ins., 10 ins. in ground, for $\frac{1}{4}$ Sec. Cor., 100 ft. above ravine, marked $\frac{1}{4}$ on W. face; from which A fir, 9 ins. diam., brs. N.22°E., 20 lks. dist., marked $\frac{1}{4}$ S B T. A fir, 12 ins. diam., brs. S.75°W., 12 lks. dist., marked $\frac{1}{4}$ S B T.
43.50	Top of low ridge brs. E. & W., 50 ft. above $\frac{1}{4}$ Sec. Cor.
46.80	Ravine, course E., 50 ft. below top of ridge.
50.25	Top of ridge, brs. E. & W., 100 ft. above ravine.
54.00	Ravine, course E., 100 ft. below top of ridge.
59.25	Top of ridge brs. E. & W., 100 ft. above ravine.
64.50	Branch, 4 lks. wide, in ravine runs S.E., 400 ft. below top of ridge and ascend.
80.00	Set basalt stone, 14 x 13 x 6 ins., 11 ins. in ground, for Cor. to Secs. 30, 31, 25 & 36, 300 ft. above branch, marked with 1 notch on S. and 5 notches on N. edges; from which A pine, 32 ins. diam., brs. N.60°W., 71 lks. dist., marked T 5 N R 38 E S 25 B T., and raised mound of stone alongside.