Dependent Resurvey E. Bdy., T 5 N R 38 E W M.

Chains	marked
	marked
	1 S 36
	1932
	from which
44	A fir, 12 ins. diam., brs. S.50°W., 238 lks. dist., marked 2 S 36 B T.
	A fir, 5 ins. diam., brs. N.20°W., 72 lks. dist., marked \$ S 36 B T.
	Thence
	N., continuing measurements.
	Continue to asc. 81 ft. over S.E. slope.
44.50	Small rounding spur, skopes E.; desc. 73 ft. over NE. slope
63.10	Dry creek bed, 5 lks. wide, course SE.; asc. 683 ft. over
	SW. slope.
79.47	The old Cor.; established for Secs. 25, 30, 31 & 36; de-
	termined by reference to record bearings & distances
	from the old bearing trees.
	I now change this Cor. to refer to Secs. 25 & 36 only.
	2 300 03330 032 00 10 20 00 00 00 00 00 00 00 00 00 00 00 00
	At point for Cor.
ē	Set an iron post, 3 ft. long, 2 ins. diam., 6 ins. in the
	ground to solid rock and in mound of stone to top, for Cor. to Secs. 25 & 36 only, with brass cap, marked
5 .	The state of the s
	T5N S25 T5N R39E
	S36 [83]
	R38E 1932
	from which
	An interpolation states after the second of the state of the second of t
80	A pine, 38 ins. diam., brs. N.32°E., 203 lks. dist., marked T 5 N R 39 E S 30 B T. (Old B. T.)
4	A rotted fir stump, brs. S.152°E., 231 lks. dist., normarks. (Old B. T.)
	A pine, 34 ins. diem., brs. N.16°W., 202 lks. dist., marked T 5 N R 38 E S 25 B T. (Old B T.)
	No new bearing tree available for Sec.36.
	Obliterate the marks on the old bearing trees refer-
	ring to T 5 N R 39 E.
	And the state of t
	Land; mountainous. Soil; rocky loam; 3rd rate.
7 200	Timber; fir, spruce, tamarack, pine & yew.
	Timber; fir, spruce, tamarack, pine & yew. Undergrowth; vinemaple, alder, hunkleherry, laurel, mountai ash, willow and Oregon grape.