

Dependent Resurvey E. Bdy., T 5 N R 38 E W M.

Chains

- A spruce, 24 ins. diam., brs. S.57°E., 25 lks. dist., marked  $\frac{1}{4}$  S 7 B T. (Old B.T.)
  - A spruce, 36 ins. diam., brs. S.70°W., 47 lks. dist., marked  $\frac{1}{4}$  S 12 B T. (Old B.T.)
  - A spruce, 16 ins. diam., brs. N.21°W., 59 lks. dist., marked  $\frac{1}{4}$  S 12 B T. (Old BT)
- Obliterate the marks on the old SE bearing tree.

Thence

N.0°12'E., continuing measurements.

Desc. 61 ft. over NW. slope.

- 44.40 Head of ravine, course W.; asc. 33 ft. over SW. slope.
- 51.10 Spur, slopes W.; desc. 238 ft. over NW. slope.
- 57.15 Ravine, course NW.; asc. 28 ft. over SW. slope.
- 59.05 Spur, slopes W.; desc. 123 ft. over NW. slope.
- 66.80 Creek, 1 lk. wide, course SW.; asc. 269 ft. over SW. slope.
- 75.20 Spur, slopes NW.; desc. 30 ft. over NW. slope.
- 77.40 Ravine, course NW.; asc. 2 ft. over SW. slope.
- 79.29 The original Cor. established for Secs. 1, 6, 7 & 12, which is an iron stone, 20 x 14 x 6 ins., firmly set, marked with 1 notch on N., and 5 notches on S. edges.

I now change this Cor. to refer to Secs. 1 & 12 only.

At point for Cor.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for Cor. to Secs. 1 & 12 only, with brass cap, marked

T5N		T5N
S 1		R39E
S12		S 7
R38E		
		1935

from which

- A fir, 36 ins. diam., brs. N.25°E., 129 lks. dist., marked T 5 N R 39 E S 6 B T. (Old B.T.)
  - A fir snag, 34 ins. diam., brs. S.26°E., 95 lks. dist., marked T 5 N R 39 E S 7 B T. (Old B.T.)
  - A dead fir, 24 ins. diam., brs. S.88°W., 58 lks. dist., marked T 5 N R 38 E S12 B T. (Old B.T.)
  - A fir, 54 ins. diam., brs. N.5°W., 90 lks. dist., marked T 5 N R 38 E S 1 B T. (Old B.T.)
- Obliterate the marks on old bearing trees referring to T 5 N R 39 E.
- A spruce, 48 ins. diam., brs. S.81 $\frac{1}{2}$ °W., 87 lks. dist., marked T 5 N R 38 E S 12 B T. (New B T.)

Land; mountainous.  
Soil; sandy loam, 3rd rate.