Exterior Lines of T. 5 S., R. 29 E. W.M.

	Chains		Feet
		N. bet. Secs. 25 and 30,	
		Var. 21° E	
		Undulating,	. (
	40.00	Set a basalt stone 18 x 8 x 7 ins., 12 ins. in ground, on	
	a ka	level for \$\frac{1}{4} Sec. Cor., marked \$\frac{1}{4}\$ on N. face, from which,	
		A Pine 22 ins. diam. brs. S. 52° E. 52 lks. dist.	
		marked & S.B.T.	
		A Pine 9 ins. diam. brs. N. 34° W., 47 lks. dist.	
		marked & S.B.T.	
	80.00	Set a basalt stone 17 x 12 x 4 ins., 12 ins. in ground for	
		Cor to Secs. 24, 25, 19 and 30, marked with,	
		N 4 355	
9	50	2 notches on S. and d notage to	
		4 notches on N. edges, from which,	
		A Tamarack 6 ins. diam. brs. N. 44° E. 88 lks. dist.	
		marked T. 5 S., R. 30 E., S. 19 B.T.	(
		A Pine 20 ins. diam. brs.S. 75° E. 76 lks. dist.	
		marked T. 5 S. R. 30 E., S. 30 B.T.	
		A Pine 14 ins. diam. brs. S. 83° W. 63 lks. dist.	
		marked T. S S., R. 29 E., S. 25 B.T.	
		A Fir 8 ins. diam. brs. N. 18° W. 44 lks. dist.	
		marked T. 5 S., R. 29 E., S. 24 B.T.	- 2
3	9 1	Land; surface undulating,	= <x< td=""></x<>
		Soil; 2nd and 3rd rate, heavily timbered with Pine,	
		Tamarack and Fir, with some open glades.	
	8 7		
	. 4	N. bet. Secs. 24 and 19,	
	7.1	Var. 17° E.	
	40.00	Set basalt stone 15 x 8 x 6 ins. 10 ins. in ground, on	
		slight S. slope for \(\frac{1}{4} \) Sec. Cor., marked \(\frac{1}{4} \) on W. face,	
		from which,	
	10	A Pine 10 ins. diam. brs. E. 54 lks. dist.	
	70	marked 2 S.B.T.	
(1)	(9)	A Pine 20 ins. diam. brs. N. 44° W. 12 lks. dist.	
		marked & S.B.T.	1.0
	80.00	Set a basalt stone 18 x 10 x 8 ins. 12 ins. in ground for	
		Cor. to Secs. 13, 18, 19 and 24, marked with,	L