Subdivisional Lines of T. 5 S., R. 30 E., W.M.

-	Chains	Fe	et
		x 10 x 10 ins. 10 ins. in ground for $\frac{1}{4}$ Sec. Cor.,	
		marked $\frac{1}{4}$ on N. face, and raised a mound of stone alongside.	•
	79.60	The Cor. to Secs. 13, 14, 23 and 24.	$\langle \cdot \rangle$
		Land; rolling,	6
	±	Soil; 2nd rate. Densely covered with forests of Pine &	
100	-	Fir timber, 79.60 Chs.	
		May 19, 1883.	
	- S89 - SS	ш эх	
	B .	N. bet. Secs. 13 and 14.	
		Var. 22° E.	
	26.00	Brook, 5 lks. wide, runs E.	
	40.00	Set basalt stone 12 x 10 x 10 ins., 8 ins. in ground for	
		\$ Sec. Cor., marked \$ on W. face, from which	
	10	A Pine 40 ins. diam. brs. S. 38° W., 63 lks. dist.	
		marked 4 S.B.T.	Sec.
		A Pine 10 ins. diam. brs. S. 41° E., 276 lks. dist.	1
		marked & S.B.T.	U
	70.50	Brook, 5 lks. wide, runs E.	
	80.00	Set a post 4 ft. long 4 ins. sq. 24 ins. in ground for Cor.	
		to Secs. 11, 12, 13 and 14, marked,	
	2	T. 5 S., S. 12 on N.E.	
		R. 30 E., S. 13 on S.E.	
		S. 14 on S.W.	
		S. 11 on N.W., faces with,	
		4 notches on S., and	
		linotch on E. edges, from which	
		A Pine 30 ins. diam. brs. S. 38° E., 10 lks. dist.	
		marked T. 5 S., R. 30 E., S. 13 B.T.	
334	1 2	A Pine 20 ins. diam. brs. N. 69° W. 53 lks. dist.	1
		marked T. 5 S., R. 30 E., S. 11 B.T.	
		A Pine 30 ins. diam. brs. S. 18° W. 83 lks. dist.	
		marked T. 5 S., R. 30 E., S. 14 B.T.	
		No tree within limits in Sec. 12, dug pit 18 x 18 x 12 ins.	
		5½ ft. dist. and raised mound of earth 2 ft. high, 4½ ft.	10 10
		base alongside.	
	1	Tonda malling	