Chains	8 8 8 8 8 8 8
	Fe
	5 notches on W. edges, from which,
	A Pine 8 ins. diam. brs. N. 79° W. 226 lks. dist.
	marked T. 4 S., R. 30 E., S. 35 B.T., and a mound
€0	of stone alongside in liew of pits, no other trees near.
	S. 0° 21' E. on true line bet. Secs. 1 and 2, with same
40.30	var.
	Set basalt stone 20 x 15 x 9 ins., 15 ins. in ground for
	\$ Sec. Cor. marked \$\frac{1}{4}\$ on W. face, from which,
	A Pine 36 ins. diam. brs. N. 45° E., 43 lks. dist.
	marked 1 S.B.T.
	30000000000000000000000000000000000000
	A Pine 24 ins. diam. brs. S. 35° W., 52 lks. dist.
	marked & S.B.T.
80.30	The Cor. to Secs. 1, 2, 11 and 12
	Land; rolling,
	Soil; rocky, 3rd rate, densely covered with forests of
	Yellow Pine timber, 80.30 Chs.
	May 20, 1883.
	From the Standard Cor. to Secs. 34 and 35, on the S. Bdy.
	of Tp. which is a basalt stone 15 x 12 x 4 ins. firmly
	set in ground marked, S.C. with,
	Particular Controller Supplier Controller Supp
	2 notches on E., and
	4 8
	2 notches on E., and 4 notches on W. edges, from which,
	2 notches on E., and 4 notches on W. edges, from which, A Pine 20 ins. diam. brs. N. 36° E., 168 lks. dist.
	2 notches on E., and 4 notches on W. edges, from which, A Pine 20 ins. diam. brs. N. 36° E., 168 lks. dist. marked T. 5 S., R. 30 E., S. 35 S.C.B.T.
	2 notches on E., and 4 notches on W. edges, from which, A Pine 20 ins. diam. brs. N. 36° E., 168 lks. dist. marked T. 5 S., R. 30 E., S. 35 S.C.B.T. No tree on N.W., and a mound of stone 3 ft. in diam. and
	2 notches on E., and 4 notches on W. edges, from which, A Pine 20 ins. diam. brs. N. 36° E., 168 lks. dist. marked T. 5 S., R. 30 E., S. 35 S.C.B.T. No tree on N.W., and a mound of stone 3 ft. in diam. and 18 ins. high around cor., I run,
	2 notches on E., and 4 notches on W. edges, from which, A Pine 20 ins. diam. brs. N. 36° E., 168 lks. dist. marked T. 5 S., R. 30 E., S. 35 S.C.B.T. No tree on N.W., and a mound of stone 3 ft. in diam. and 18 ins. high around cor., I run, N. bet. Secs. 34 and 35,
10.00	2 notches on E., and 4 notches on W. edges, from which, A Pine 20 ins. diam. brs. N. 36° E., 168 lks. dist. marked T. 5 S., R. 30 E., S. 35 S.C.B.T. No tree on N.W., and a mound of stone 3 ft. in diam. and 18 ins. high ground cor., I run, N. bet. Secs. 34 and 35, Var. 20½° E.
40.00	2 notches on E., and 4 notches on W. edges, from which, A Pine 20 ins. diam. brs. N. 36° E., 168 lks. dist. marked T. 5 S., R. 30 E., S. 35 S.C.B.T. No tree on N.W., and a mound of stone 3 ft. in diam. and 18 ins. high around cor., I run, N. bet. Secs. 34 and 35, Var. 20½° E. Set a Fir post 3 ft. long, 3 ins. sq. 24 ins. in ground
10.00	2 notches on E., and 4 notches on W. edges, from which, A Pine 20 ins. diam. brs. N. 36° E., 168 lks. dist. marked T. 5 S., R. 30 E., S. 35 S.C.B.T. No tree on N.W., and a mound of stone 3 ft. in diam. and 18 ins. high around cor., I run, N. bet. Secs. 34 and 35, Var. 20½° E. Set a Fir post 3 ft. long, 3 ins. sq. 24 ins. in ground for ½ Sec. Cor., marked ½ S. on W. face; from which,
40.00	2 notches on E., and 4 notches on W. edges, from which, A Pine 20 ins. diam. brs. N. 36° E., 168 lks. dist. marked T. 5 S., R. 30 E., S. 35 S.C.B.T. No tree on N.W., and a mound of stone 3 ft. in diam. and l8 ins. high around cor., I run, N. bet. Secs. 34 and 35, Var. 20½° E. Set a Fir post 3 ft. long, 3 ins. sq. 24 ins. in ground for ½ Sec. Cor., marked ½ S. on W. face; from which, A Tamarack 6 ins. diam. brs. S. 82° E., 14 lks. dist.
40.00	2 notches on E., and 4 notches on W. edges, from which, A Pine 20 ins. diam. brs. N. 36° E., 168 lks. dist. marked T. 5 S., R. 30 E., S. 35 S.C.B.T. No tree on N.W., and a mound of stone 3 ft. in diam. and 18 ins. high around cor., I run, N. bet. Secs. 34 and 35, Var. 20½° E. Set a Fir post 3 ft. long, 3 ins. sq. 24 ins. in ground for ½ Sec. Cor., marked ½ S. on W. face; from which,

marked \frac{1}{4} S.B.T.