Subdivisional Lines of T. 5 S., R. 30 E., W.M.

	Chains	I.	eet
		Thence I run,	
5	E 2	S. 0° 20' E. on true line bet. Secs. 3 and 2 with same Var.	
	40.02	Set basalt stone 12 x 8 x 8 ins. 8 ins. in ground for \(\frac{1}{4} \)	
		Sec. Cor., marked \(\frac{1}{4} \) on W. face, from which	
		A Pine 40 ins. diam. brs. N. 43° E., 111 lks. dist.	
		marked & S.B.T.	
		No other trees within limits and raised mound of stone	
		alongside.	
	80.02	The Cor. to Secs. 2, 3, 10 and 11.	
	00.00	Land; rolling.	
		Soil; 3rd rate. Densely covered with forests of Pine and	
		Fir 80.02 Chs.	
		From the Standard Cor. to Secs. 33 and 34, on the S. bdy of	
		the Tp. which is a pine post 4 ft. long, 4 ins. sq.,	1
		firmly set in the ground marked,	
28		S.C.T. 5 S.R. 30 E. on N.	
		S. 34 " E., and	
	-	S, 33 " W., faces,	
		with 3 notches on E. and W. edges, from which,	
		A Tamarack 10 ins. diam. brs. N. 38° W. 10 lks. dist.	a.
	8.	marked T. 5 S., R. 30 E., S. 33 B.T.	
		A Fir 5 ins. diam. brs. N. 31° E., 19 lks. dist.	
	545 02	marked T. 5 S., R. 30 E., S. 34 B.T.	
		I run,	
		N. bet Secs. 33 and 34.	
		Var. 20° E.	
	40.00	Set basalt stone 20 x 18 x 12 ins., 15 ins. in ground for	
		\$ Sec. Cor., marked \$ on W. face, from which,	
		A Fir 20 ins. diam. brs. S. 25° W. 94 lks. dist.	
		marked 4 S.B.T.	
		A Pine 30 ins. diam. brs. N. 57° E., 75 lks. dist.	
		marked 4 S.B.T.	20
	70.00	Descend hill, course N.E. and S.W.	
	80.00	To a point about 150 ft. bellow top of hill. Set a basalt	10.75