X

	Chains	marked T.5 S., R.33 E., S.1, B.T.
		Destroyed marks referring to Secs. 6 & 7.
	EE 00	Enter creek bottom, brs. E. & W., 250 ft. below Cor.
(4)	53.00	201
20	54.50	The 4 Sec. Cor.
	57.50	Camas Creek, 20 lks. wide, runs W.
	59.00	Leave bottom and ascend hill.
	72.00	Top of hill, brs. E. & W.
	80.00	Set post, 5 ft. long, 5 ins. sq., in stony ground, and ra
		raised mound of stone; 3 ft. high and 5 ft. base around
	10 10 00	post, for Cor. to Tps. 4 & 5 S., Rs. 33 E., marked
		T.4 S., R. 33 E., S. 34 on N.E.
		T.5 S., R. 33 E., S. 3 on S. E.
	200 E	with 6 notches on N.& S. edges
		and 3 notches on E. edge.
2		This Cor. is 14.31 chs. S. of Cor. to Tps. 4 & 5 S., R.33 E. Land; mountainous. Soil; 1st & 2nd rate. Timber; scattering Langing and fires.
		Subdivisional Lines, T.5 S., R.33 E., W. M. As surveyed by Geo. S. Pershin, U.S. Deputy Surveyor, Under Contract No. 430, Ass. Dated March 23, 1882.
		Preliminary to commencing survey, I run N. on E. Bdy. of
		Sec. 36, and at 79.92, the Cor. to Secs. 25 & 36. Then
		W. on S. Bdy. of Sec. 36 and at 39.98, the \$ Sec. Cor.
		and at 79.95 the Sec. Cor. to Secs. 35 & 36.
	37 1527-	My compass runs the same lines and my chaining is practicell
		ally the same as that of the Standard and exteriors.
		Survey commenced May 29, 1882 with Burt's improved Solar
		Compass, Young of Philadelphia, maker, - in good order
		and adjustment.
	68	I begin at the stone, about 6 ins. out of ground, Cor. to
		Secs. 35 & 36, on S. Bdy. of Tp.
		A tamarack, 16 ins. diam., brs. N.75°E., 211 lks. dist.,
		marked T.5 S., R.33 E., S.36, B.T., S.C.
		A pine, 6 ins. diam., brs. N.38°W., 76 lks. dist.,
()	#2.00	marked T.5 S., R.33 E., S.35, S.C., B.T.
		N. bet. Secs. 35 & 36.
	1.4	Ascending.