Chains	marked T.5 S., R.34 E., S.31, B.T.
aut 11 s	A pine, 5 ins. diem., brs. S.45°W., 10 lks. dist.,
	marked T.5 S., R.33 E., S.36 ,B.T.
gar stra	A pine, 10 ins. diam., brs. N.85°W., 50 lks. dist.,
	marked T.5 S., R.33 E., S.25, B.T.
39.92	from which Cor. I run
	N.89°29'W. on true line bet. Secs. 25 & 36.
	Var. 19°15'E.
	Set basalt stone, 16 x 8 x 7 ins., 11 ins. in ground, on
	S. slope, for \(\frac{1}{2}\) Sec. Cor., marked \(\frac{1}{2}\) on N. side.
o A	A pine, 14 ins. diam., brs. N.64°E., 36 lks. dist.,
	marked & S., B.T.
	A pine, 10 ins. diam., brs. S.36°W., 48 lks. dist.,
	marked & S., B.T.
TO 04:	
79.64	The Cor. to Secs. 25, 26, 35 & 36.
	Land; surface mountainous.
	Soil; 3rd rate.
	Mostly heavily timbered with pine, fir & tamarack timber
	with underbrush same. Some open glades.
	N. bet. Secs. 25 & 26.
	Var.20°15'E.
7.00	Top of rise & begin steep descent.
40.00	Set tamarack post, 4 ft. long, flattened to 3 ins. thick
	ness, on E. face of ridge, marked 4 S. on W. face, fo
	½ Sec. Cor.
	A fir, 20 ins. diem., brs. S.54°E., 25 lks. dist.,
	marked & S.,B.T.
	A fir, 20 ins. diam., brs. N.48°W., 8 lks. dist.,
. •	marked & S.,B.T.
77.00	Creek, 100 lks. wide, course N.W., descent 600 ft., from
gair a	top of bluff.
80.00	Set basalt stone, 16 x 12 x 5 ins., 11 ins. in ground, or
(1)	level, in creek bottom, marked with 2 notches on S. &
	1 notch on E. edges; for Cor. to Secs. 23, 24, 25 & 20
	from which,
	ō.