

Subdivisional Lines, T.5 S., R.33 E., W. M.

Chains	
	This corner sets a basalt stone, in mound of stone, projecting about 6 ins.
	A pine, 6 ins. diam., brs. N.46°E., 19 lks. dist., marked T.5 S., R.33 E., S.32, B.T.
	A pine, 40 ins. diam., brs. N.67°W., 39 lks. dist., marked T.5 S., R.33 E., S.31, B.T.
14.50	Leave timber, coarse E. & W., enter small prairie.
40.00	Set basalt stone, 14 x 10 x 6 ins., 10 ins. in ground, on level, for $\frac{1}{4}$ Sec. Cor., marked $\frac{1}{4}$ on W. face. A pine, 20 ins. diam., brs. N.48°E., 28 lks. dist., marked $\frac{1}{4}$ S., B.T.
	A pine, 42 ins. diam., brs. N.46°W., 92 lks. dist., marked $\frac{1}{4}$ S., B.T.
40.50	Enter timber, coarse, S.E. & N.W.
80.00	Set basalt stone, 18 x 12 x 7 ins., 12 ins. in ground, on level, for Cor. to Secs. 29, 30, 31 & 32, marked with 1 notch on S. and 5 notches on E. edges, A tamarack, 12 ins. diam., brs. N.64°E., 15 lks. dist., marked T.5 S., R.33 E., S.29, B.T.
	A tamarack, 10 ins. diam., brs. S.82°E., 45 lks. dist., marked T.5 S., R.33 E., S.32, B.T.
	An alder, 8 ins. diam., brs. S.88°W., 43 lks. dist., marked T.5 S., R.33 E., S.31, B.T.
	A tamarack, 12 ins. diam., brs. N.17°W., 57 lks. dist., marked T.5 S., R.33 E., S.30, B.T.
	Land; surface undulating.
	Soil; 2nd & 3rd rate.
	Pine, tamarack & fir timber, heavy on N. $\frac{1}{2}$ mile, S. $\frac{1}{2}$ mile mostly open.
	June 5, 1882.
	E. on random line bet. Secs. 29 & 32.
	Var. 20°30'E.
40.00	Set temp. $\frac{1}{4}$ Sec. Cor.
79.48	Intersected N. & S. line, 22 lks. N. of Cor. to Secs. 28, 29, 32 & 33. Ascent 100 ft., from which Cor., I run