Chains	N. bet. Secs. 19 & 20.
	3000 30000000
	Var.20°00'E.
	Slightly descending.
40.00	
	\$ Sec. Cor., marked \$ onnW. side; raised mound of stone
	alongside.
80.00	Set post, 4 ft. long, 4 ins. sq., in mound of stone, for
	Cor. to Secs. 17, 18, 19 & 20, marked
	T.5 S., S.17 on N.E.
	R.33 E.,S.20 on S.E.
	S.19 on S.W. and
	S.18 on N.W., also
	3 notches on S. and
100	. 5 notches on E. edges, also
	Set basalt stone, in mound, 16 x 10 x 7 ins., marked with
1	3 notches on S. and 5 notches on E. edges. Descent about
	80. ft.
	Land; surface undulating, and sloping N.
19	Soil; 2nd & 3rd rate.
	A few small groves of pine timber on this mile, good grass
20.74	June 6, 1882.
1 × 2 × 2 ±	E. on random line bet. Secs. 17 & 20.
	Var.18°15'E.
14.25	Spring branch, course N.W.
40.00	Set temp. 1 Sec. Cor.
61.00	On ridge, course N.W. & S.E.; creek bluff, ascent about 20
	soft. The second second second second
. 80.04	Intersected N. & S. line, 12 lks. N. of Cor. to Secs. 16,
	17, 20 & 21, descent about 200 ft., from which Cor., I
A <sup>C</sup>	run
	N.89°55'W. on true line bet. Secs. 17 & 20.
	Var.19°15'E.
40.02	Set basalt stone, 16 x 10 x 8 ins., 11 ins. in ground, on
1400 200000	W. slope, for & Sec. Cor., marked & on N. face.
20 10	AND MANAGEMENT CONTRACTOR CONTRACTOR CONTRACTOR TO THE CONTRACTOR