First Standard Parallel S., thru Range 33½ East (S. Bdy., T.5 S.,R.33½ E.,W. M.)
As surveyed by Rufus S. Moore, U.S.Deputy Surveyor, Under Contract No. 451,
Dated June 12, 1882.

Chains	First standard parallel S., through R. 34 E., survey com-
.=.(6)	menced Oct. 12, 1882, with a Burt's improved Solar compass.
	I begin at the standard Cor. to Secs. 31 & 32, T.5 S., R.34
4	E., which is a post, 4 ins. sq., marked
	S.C., T.5 S., R.34 E. on N.
	S.32 on E. and
	S.31 on W. faces, with
	5 notches on E. and
	1 notch on W. faces, from which
	A tamarack, 14 ins. diam., brs. N.45°E., 23 lksdist.
	marked T.5 S., R.34 E., S.32, B.T.
	A tamarack, 11 ins. diam., brs. N.30°W., 24 lks. dist.
	marked T.5 S., R.34 E., S.31, B.T.
a - a - 1	Thence I proceed to connect the 1st standard parallel S.
X = 1+	with that portion of the same, which was run from the
	W., terminating at E. Bdy. of R.33 E., I run
	W. on S. Bdy. of Sec.31.
g*	Var.202°E.
5.00	Descend about 400 ft. to
31.50	Creek, 8 lks. wide, runs N.20°W. Ascend abruptly from cree
	along hillside sloping N.E., about 125 ft. to
40.00	Set post, 3 ft. long, 3 ins.sq., 24 ins. in ground, for
	standard & Sec. Cor., marked S.C. & S. on N. face, from
000	which
	A fir, 18 ins. diem., brs. N.27°E., 18 lks. dist.,
	marked S.C. 2 S., B.T.
	A hemlock, 22 ins. diam., brs. S.132°W., 24 lks. dist.
	marked S.C. 1 S., B.T.
80.00	Set post, 42 ft. long, 4 ins. sq., 24 ins. in ground, for
	standard Cor. to T.5 S., Rs. 331 & 34 E., marked
	S.C., T.5 S on N.
	R.34 E.,S.31 on E.
187	R.332 E.,S.36 on W. faces, with
	6 notches on N., E. & W. edges, from which
	The state of the s