

S. Bdy., T.5 S., R.33 $\frac{1}{2}$ E., W. M.

Chains	W. on S. Bdy. of Sec. 34. Var. 20° E.
11.00	Top of ridge, brs. N.W. & S.E., 400 ft. high & descend.
24.01	To a point, 1728 lks. S. of Cor. to Tps. S., R.33 E., which is a post, 4 ins. sq., marked T.5 S., R.34 E., S.31 on N.E. which I changed to R.33 $\frac{1}{2}$ E., S.34. T.5 S., R.33 E., S.36 on N.W. faces, with 6 notches on N., E. & W. edges, from which,
	A tamarack, 8 ins. diam., brs. N.64°W., 56 lks. dist., marked T.5 S., R.33 E., S.36, B.T.
	A fir, 10 ins. diam., brs. N.48°E., 35 lks. dist., marked T.5 S., R.34 E., S.31, B.T.
	I changed the marks on this last bearing tree from R.34 E. to R.33 $\frac{1}{2}$ E. and the Sec. from 31 to 34.
	Where, I set post, 5 ft. long, 5 ins. sq., 24 ins. in ground, for Closing Cor. to Tps 5 S., R.33 $\frac{1}{2}$ E., marked T.5 S., C.C. on N.
	R.33 $\frac{1}{2}$ E., S.34, S.C. on E. and
	T.6 S. on W. faces, with 6 notches on N. & S. and 3 notches on E. edges, from which
	A fir, 12 ins. diam., brs. S.22°E., 31 lks. dist., marked T.6 S., S.C., C.B.T.
	A fir, 8 ins. diam., brs. N.62°W., 8 lks. dist., marked T.6 S., S.C., C.B.T.
	A fir, 12 ins. diam., brs. S.40°W., 37 lks. dist., marked T.6 S., S.C., C.B.T.
	Land; mountainous.
	Soil; 2nd rate.
	Heavily timbered with pine, fir & tamarack.
	Dense pine & fir undergrowth.
	W. Bdy. of T.5 S., R.34 E., W. M. As surveyed by the same U.S. Deputy Surveyor, Under same Contract & date.
	I begin at the standard Cor. to T.5 S., R.33 $\frac{1}{2}$ & 34 E., which is a post, 4 $\frac{1}{2}$ ft. long, 4 ins. sq., marked T.5 S., S.C.