## Subdivisional Lines of T. 6 S., R. 31 E., W.M.

Che	ins
2	Scattering pine, fir and tamarack timber, except the W.
	30 Chs. of E. 2 and E. 2 of W. 2.
	Heavy pine, fir and tamarack. Dense undergrowth of pine,
10	fir and tamarack and mountain laural.
G _0	N. bet. Secs. 10 and 11
пэф	Var. 21° E.
4	.50 Top of ridge, brs. N.W. and S.E.
20	.80 Bridge creek, 25 lks. wide, runs W.
	Foot of hill, brs. E. and W.
21	.25 Ascend hill, brs. E. and W.
36	.25 Top of ridge, brs. N.E. and S.W.
40	.00 Set a basalt stone, 16 x 7 x 7, and made mound of stone
	k sec. Cor., from which
	A Fir, 30 ins. in diam. brs. S. 39° W., 63 lks. dist
. 64	.00 Creek, 15 lks. wide, runs. S. 15° W.,
	Foot of hill, brs. S. 15° W., N. 15° E.
	Ascend hill from creek, brs. N. 15° E., S. 15° W.
80	.00 Set a basalt stone, 16 x 12 x 8, and mound of stone for
	Cor. to Secs. 2, 3, 10 & 11.
	Land; rolling and broken
	Soil; 3rd rate.
	Scattering pine and fir timber, except on creek, heavy
	pine, fir, tamarack and dense young pine, fir, and
V- 95	tamarack.
8	E. on a random line bet. 2 & 11
4	.00 Set a temp. 1 Sec. Cor.
1	.53 Intersect N. and S. line, 165 lks. S. of Cor. to Secs. 1,
	2, 11 & 12, from which Cor. I run
	0.000 404 W
16	
	.63 Ravine, course N.W.
40	.26 Set a basalt stone, 14 x 8 x 5, and made mound of stone
	½ Sec. Cor.
60	.53 Top of hill, brs. N. and S28 Foot of hill, brs. N. 15° E., S. 15° W

VIENAM 15674