Exterior Lines, T 6 S R 32 E W M.

	7
	A fir, 12 ins. diam., brs. N.40°W., 12 lks. dist.,
	marked 1 3 B T.
4	Thence over gently rolling ground.
80.00	Set basalt stone, 16 x 12 x 8 in., 10 ins. in ground, for
	Cor. to Secs. 19, 24, 25 & 30, marked with 4 notches
	on N. and 2 notches on S. edges, from which
	A tamarack, 18 ins. diam., brs. N.35°E., 14 lks. dist.
n 1	marked T 6 S R 33 E S 19 B T.
	A pine, 24 ins. diem., brs. S.15°W., 84 lks. dist.,
	marked T 6 S R 32 E S 25 B T.
	A pine, ll ins.diam., brs.S. 65°E., 94 lks. dist.,
	marked T 6 S R 33 E S 30 B T.
	A pine, 7 ins. diam., brs. N.10°W., 7 lks. dist.,
	SI RE PRODUCTION OF THE PRODUCTION OF T
	marked T 6 S R 32 E S 24 B T.
	Land; mountainous.
	Soil; 2nd rate.
9 8	Densely covered with forests of pine, fir & tamarack tim-
	ber, 80 chs.
	Thick undergrowth of balm, spruce, fir & tamarack, 80 chs.
3.5	N. bet. Secs. 24 & 19.
	Var.20°E.
	Var.20°E. Descend over rolling ground.
39.00	y agreem a commencer mass
39.00 40.00	Descend over rolling ground.
	Descend over rolling ground. Foot of descent, creek 6 lks. wide, course W.
	Descend over rolling ground. Foot of descent, creek 6 lks. wide, course W. Set fir post, 3 ft. long, 3 ins. sq., 24 ins. in ground,
	Descend over rolling ground. Foot of descent, creek 6 lks. wide, course W. Set fir post, 3 ft. long, 3 ins. sq., 24 ins. in ground, for \(\frac{1}{4} \) Sec. Cor., marked \(\frac{1}{4} \) S on W. face, from which
	Descend over rolling ground. Foot of descent, creek 6 lks. wide, course W. Set fir post, 3 ft. long, 3 ins. sq., 24 ins. in ground, for \(\frac{1}{4} \) Sec. Cor., marked \(\frac{1}{4} \) S on W. face, from which A tamarack, 18 ins. diam., brs. N.66°W., 24 lks. dist.
	Descend over rolling ground. Foot of descent, creek 6 lks. wide, course W. Set fir post, 3 ft. long, 3 ins. sq., 24 ins. in ground, for \(\frac{1}{4} \) Sec. Cor., marked \(\frac{1}{4} \) S on W. face, from which A tamarack, 18 ins. diam., brs. N.66°W., 24 lks. dist. marked \(\frac{1}{4} \) S B T.
	Descend over rolling ground. Foot of descent, creek 6 lks. wide, course W. Set fir post, 3 ft. long, 3 ins. sq., 24 ins. in ground, for \(\frac{1}{4} \) Sec. Cor., marked \(\frac{1}{4} \) S on W. face, from which A tamarack, 18 ins. diam., brs. N.66°W., 24 lks. dist., marked \(\frac{1}{4} \) S B T. A fir, 10 ins. diam., brs. S.62°E., 25 lks. dist.,
40.00	Descend over rolling ground. Foot of descent, creek 6 lks. wide, course W. Set fir post, 3 ft. long, 3 ins. sq., 24 ins. in ground, for ½ Sec. Cor., marked ½ S on W. face, from which A tamarack, 18 ins. diam., brs. N.66°W., 24 lks. dist., marked ½ S B T. A fir, 10 ins. diam., brs. S.62°E., 25 lks. dist., marked ½ S B T. Leave creek bottom, ascend hill, course N.W. & E.
40.00	Descend over rolling ground. Foot of descent, creek 6 lks. wide, course W. Set fir post, 3 ft. long, 3 ins. sq., 24 ins. in ground, for ½ Sec. Cor., marked ½ S on W. face, from which A tamarack, 18 ins. diam., brs. N.66°W., 24 lks. dist., marked ½ S B T. A fir, 10 ins. diam., brs. S.62°E., 25 lks. dist., marked ½ S B T. Leave creek bottom, ascend hill, course N.W. & E. To a point, 350 ft. above creek and set basalt stone, 20 x
40.00	Descend over rolling ground. Foot of descent, creek 6 lks. wide, course W. Set fir post, 3 ft. long, 3 ins. sq., 24 ins. in ground, for ½ Sec. Cor., marked ½ S on W. face, from which A tamarack, 18 ins. diam., brs. N.66°W., 24 lks. dist., marked ½ S B T. A fir, 10 ins. diam., brs. S.62°E., 25 lks. dist., marked ½ S B T. Leave creek bottom, ascend hill, course N.W. & E.