## Subdivisional Lines, T 6 S R 32 E W M.

Chains	T - 3
40.00	Set basalt stone, 24 x 13 x 4 ins., 18 ins. in ground, for
	\$ Sec. Cor., marked \$\frac{1}{4}\$ on W. face, from which
	A fir, 6 ins. diem., brs. S.28°W., 152 lks. dist.,
	marked 2 SHB T.
	A pine, 30 ins. diam., brs. N.45°E., 149 lks. dist.,
	marked & S B T.
60.00	Enter thick brush & begin gradual descent to Camas valley.
68.50	Ravine, course S.10°E.
73.80	Intersect 1st Standard Parallel, SS, at a point 4.70 chs. E.
	of the Standard Cor. to Secs. 34 & 35, at which point I
	Set basalt stone, 18 x 15 x 8 ins., 12 ins. in ground, for
	Closing Cor. to Secs. 1 & 2, marked C.C. with 1 notch
	on E, and 5 notches on W. edges, from which
	A tamarack, 20 ins. diam., brs. S.31°E., 27 lks. dist.
	marked T 6 S R 32 E S 1 B T.
100	A pine, 10 ins. diem., brs. S.78°W., 141 lks. dist.,
	marked T 6 S R 32 E S 2 B T.
	Land; mountainous.
	Soil; 2nd rate.
	Densely covered with forests of pine, fir & tamarack tim-
	ber, 73.80 chs.
20%	Occasional thickets of pine & fir brush.
	June 7th 1883.
\$650N	
	From the Cor. to Secs. 2, 3, 34 & 35, on S. Bdy. of Tp.,
	which is a fir post, 4 ins. sq., firmly set in ground,
	marked
ea II ja	T 6 S S 35 on N.E.
	R 32 E S 2 on S.E.
	T 7 S S 3 on S.W and
	S 34 on N.W. faces, with
	2 notches on B. and

from which

A fir, 10 ins. diam., brs. N.74°E., 27 lks. dist., marked T 6 S R 32 E S 35 B T.

4 notches on W. edges,