

Subdivisional Lines, T 6 S R 32 E W M.

	Chains	
		$\frac{1}{4}$ Sec. Cor., marked $\frac{1}{4}$ on N. face, from which A fir, 18 ins. diam., brs. N.8°W., 11 lks. dist., marked $\frac{1}{4}$ S B T. A fir, 24 ins. diam., brs. S.25°E., 10 lks. dist., marked $\frac{1}{4}$ S B T.
80.30		The Cor. to Secs. 22, 23, 26 & 27. Land; mountainous, & rolling. Soil; 2nd rate. Densely covered with forests of pine, fir & tamarack timber, 80.30 chs. Occasional thickets of balm, fir & pine brush.
		N. bet. Secs. 22 & 23.
		Var. 20°E. Gently ascend along hillside, facing W.
14.00		Brook, 3 lks. wide, course W., about 100 ft. below Cor. & ascend abruptly, a rocky hill, course N.W. & S.E.
17.00		Leave timber, course E. & W.
40.00		To a point, about 300 ft. above brook, and Set basalt stone, 10 x 8 x 8 ins., 7 ins. in ground, for $\frac{1}{4}$ Sec. Cor., marked $\frac{1}{4}$ on W. face, and raised mound of stone, $1\frac{1}{2}$ ft. high, $3\frac{1}{2}$ ft. base alongside.
45.00		Enter dense timber, course E. & W.
80.00		Set basalt stone, 24 x 15 x 12 ins., 18 ins. in ground, for Cor. to Secs. 14, 15, 22 & 23, marked with 3 notches on S. and 2 notches on E. edges, from which A pine, 24 ins. diam., brs. N.16°E., 22 lks. dist., marked T 6 S R 32 E S 14 B T. A pine, 24 ins. diam., brs. S.3°E., 148 lks. dist., marked T 6 S R 32 E S 23 B T. A pine, 24 ins. diam., brs. S.43°W., 134 lks. dist., marked T 6 S R 32 E S 22 B T. A pine, 30 ins. diam., brs. N.12°W., 34 lks. dist., marked T 6 S R 32 E S 15 B T.
		Land; mountainous.