Subdivisional Lines, T 6 S R 32 E W M.

Chains	1 2 2 40	
	W. on random line bet. Secs. 19 & 30.	
	Var.19°E.	
5	Over rolling ground with scattering pine timber.	1
40.00	Set temp. ½ Sec. Cor.	,
81.50	Intersect W. Bdy. of Tp. at 30 lks. N. of Cor. to Secs. 19,	
	24, 25 & 30, which is a besalt stone 18 x 10 x 6 ins.,	
	in mound of stone, marked with 4 notches on N. and 2	
	notches on S. edges,	
	Thence I run	
- 10	N.89°47'E. on true line bet. Secs. 19 & 30.	
	With same Var.	
41.50	W. on random line bet. Secs. 19 & 30. Var.19°E. Over rolling ground with scattering pine timber. Set temp. ½ Sec. Cor. .50 Intersect W. Bdy. of Tp. at 30 lks. N. of Cor. to Secs. 19. 24, 25 & 30, which is a basalt stone 18 x 10 x 6 ins., in mound of stone, marked with 4 notohes on N. and 2 notches on S. edges, Thence I run N.89°47'E. on true line bet. Secs. 19 & 30. With same Var. Set basalt stone, 24 x 10 x 10 ins., 18 ins. in ground, for ½ Sec. Cor., marked ½ on N. face; dug pits, 18 x 18 x 12 ins. E. & W. of stone, 5½ ft. dist. and raised mound of earth, 1½ ft. high, 3½ ft. base alongside. The Cor. to Secs. 19, 20, 29 & 30. Land; rolling. Soil; 2md rate. Scattering pine timber, 81.50 chs. N. bet. Secs. 19 & 20. Var.19°E. Brook, 3 lks. wide, course W. """" """ Set basalt stone, 13 x 10 x 5 ins., 8 ins. in ground, for ½ Sec. Cor., marked ½ on W. face; dug pits, 18 x 18 x 12 ins., N. & S. of stone, 5½ ft. dist. and raised mound of earth, 1½ ft. high, 3½ ft. base alongside.	
S		
		-
81.50		-
=		
	N. bet. Secs. 19 & 20. Var.19°E.	
29.00	The state of the s	
30.75		
40.00	Set basalt stone, 13 x 10 x 5 ins. 8 ins. in ground, for	
de la		
80.00		-
		į
	3	5
	scattering pine timber.	